# Harlequin<sup>®</sup> torageTanks

### RELIABLE CONTAINERS

### **Tank Dimensions:**

Length: 2940mm Width: 2305mm

Overall Height: 2820mm Brimful Capacity: 8,088L Nominal Capacity: 7,683L

Net Weight: 505kg

# **Harlequin 7500FS Bunded Fuel Tank**



Harlequin Fuel Stations are the ultimate in diesel dispensing tanks and technology. Featuring forecourt style refuelling convenience and a range of added value technologies as standard, these high specification fuel tanks provide complete diesel storage and dispensing solutions.

## **Standard Features:**

- Moulded from durable medium density polyethylene material
- Integrally bunded
- Lockable equipment cabinet
- 56L/Min 230V fuel pump\*
- 10Micron particulate & water filter
- 6m delivery hose with auto shut-off dispensing nozzle
- 2" BSP(M) offset fill point c/w non-return valve & lever ball valve
- Mechanical overfill prevention valve
- 4" lockable inspection cap
- Hydrostatic contents gauge with in-cabinet digital display
- Bulkhead light
- LRC overfill prevention probe
- **Bund monitor**
- Moulded-in lifting eyes for ease of lifting
- Optional 8m cabinet mounted automatic hose reel
- **Optional** Tecalemit HDA Eco Fuel Management System

\*110V, 12V, 24V fuel pumps available. 72L/min fuel pump & fuel management system available in 230V only. Low voltage tanks have a mechanical flow meter in place of the fuel management system.

#### **Issued By:**

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL227a Issue Date: July 2024 Issue: 01 Revision 03

Auth: JC