# Harlequín<sup>®</sup> HydroStore

RAINWATER HARVESTING

### **Tank Dimensions:**

- Length: 2300mm
- Width: 1150mm
- Height: 1250mm
- Standard Invert Level: 500mm\*
- Maximum Capacity: 1460L
- Net Weight: 110kg

\*Invert level may be increased by use of risers to a maximum of 2m

## Harlequin HD1500 HydroStore Home Harvest Direct



HydroStore "Home Harvest Direct" rainwater harvesting systems consist of the HydroStore tank and the "Backup in a Box" rainwater distribution system. This allows connection of the tank to a direct plumbing system to supply appliances such as toilets, washing machines and the garden.

### **Standard Features:**

- Moulded from durable medium density polyethylene material
- 110mm inlet, outlet and service connections
- Fully secured 450mm diameter pedestrian duty manhole cover
- Integrated filter with stainless steel mesh (size 0.7 x 1.7mm)
- Calmed inlet reduces turbulence to tank sediment, improving water quality
- Pressure sensitive submersible pump (turns off if no demand), complete with integral run dry protection
- Pump can deliver up to 3.5bar pressure, with a flow rate of 2500 litres per hour.
  Max head of 35m (nominal) and power rating of 800W
- U-bend type overflow also acts as a rodent trap
- Supplied with Rain Backup in a Box control unit.
  When rainwater in the tank runs out the Backup in a Box system will top up the tank to a minimum level with mains water ensuring no interruption in supply
- Supplied with a 25m coil of 25mm HDPE pipe and 1" pump connections
- Moulded-in lifting eyes for ease of handling
- PE tank is lightweight, corrosion resistant and made from 100% recyclable material

#### **Issued By:**

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL242 Issue: 01 Revision 00