Harlequin[®] **lydroStore**

Harlequin HD5800 **HydroStore Home Harvest Direct**

RAINWATER HARVESTING

Tank Dimensions:

- Tank 1: 2300mm x 2300mm x 1250mm
- Tank 2: 2300mm x 2300mm x 1250mm

*Invert level may be increased by use of risers to a maximum of 2m

HydroStore "Home Harvest Direct" rainwater harvesting systems consist of the HydroStore tank and the "Backup in a Box" rainwater distribution system. This allows connection of the tank to a direct plumbing system to supply appliances such as toilets, washing machines and the garden.

Standard Features:

- Moulded from durable medium density polyethylene material
- 110mm inlet, outlet and service connections
- Fully secured 450mm diameter pedestrian duty manhole cover
- Integrated filter with stainless steel mesh (size 0.7 x 1.7mm)
- Calmed inlet reduces turbulence to tank sediment, improving water quality
- Pressure sensitive submersible pump (turns off if no demand), complete with integral run dry protection
- Pump can deliver up to 3.5bar pressure, with a flow rate of 2500 litres per hour. Max head of 35m (nominal) and power rating of 800W
- U-bend type overflow also acts as a rodent trap
- Supplied with Rain Backup in a Box control unit. When rainwater in the tank runs out the Backup in a Box system will top up the tank to a minimum level with mains water ensuring no interruption in supply
- Supplied with a 25m coil of 25mm HDPE pipe and 1" pump connections
- Moulded-in lifting eyes for ease of handling
- PE tanks are lightweight, corrosion resistant and made from 100% recyclable material

Issued By:

Harlequin Manufacturing Limited 21 Clarehill Road, Moira, Co. Armagh, N.Ireland, BT67 OPB

T: +44 (0)28 9261 1077 W: www.harlequin-mfg.com E: info@harlequin-mfg.com

Doc Ref: TL246 Issue Date: August 2018 Issue: 01 Revision 00 Auth: JC

Standard Invert Level: 500mm* Maximum Capacity: 5760L Net Weights: Tank 1 - 190kg Tank 2 - 190kg