

DURABLE & COMPACT

PUMP STATIONS

For Sewage/Effluent applications:

- ✓ Sewage directly from the home
- ✓ Post wastewater treatment systems
- ✓ Applications requiring a grinder pump



**AVAILABLE IN 5
DIFFERENT SIZES**
Single / Twin
Options



 @harlequinMFG

www.harlequinplastics.co.uk



A member of

BRITISH WATER

Harlequin®
MANUFACTURING FOR TOMORROW

Pump Stations



450 L Pump Station

Length 600mm
Width 600mm
Height 1,700mm
Capacity 455 litres
Population Served Extensions etc...



800 L Pump Station

Length 1,000mm
Width 1,000mm
Height 1,225mm
Capacity 820 litres
Population Served 1-5



1100 L Pump Station

Length 1,000mm
Width 1,000mm
Height 1,645mm
Capacity 1,140 litres
Population Served 1-7




1550 L Pump Station

Length 1,200mm
Width 1,200mm
Height 1,625mm
Capacity 1,600litres
Population Served 1-10



3200 L Pump Station

Length 1,200mm
Width 1,200mm
Height 3,205mm
Capacity 3,300 litres
Population Served Shared domestic or small commercial applications



Internal view of a Harlequin Pump Station



800 L Twin Model

Suitable for Domestic Use



24-hours Storage



Durable & Stable MDPE Design



Compact System




Easy to Install



Low Maintenance



Market Leading DAB Pump



Simple pipework



Flat Base for Stability



STANDARD FEATURES

- 24-hours storage for domestic applications
- 110mm inlet connection
- 50mm or 63mm outlet connection (depending on pump type)*
- 110mm services duct
- Integrated lifting eyes for ease of handling and installation
- Double sealed 600x600mm galvanised steel manhole cover, c/w locking screws
- Brass gate valve and PVC Union connection for ease of servicing
- Stainless steel pump lifting chain(s)
- Pump options available for water, effluent and sewage
- Non-return valve on all pumps
- Single and twin pump configurations
- Control panel and float switches (twin pump configurations)
- High-level alarm (twin pump configurations)
- Guide rails (grinder pumps)

	450	800	1100	1550	3200
24-hours storage for domestic applications	✓	✓	✓	✓	✓
110mm inlet connection	✓	✓	✓	✓	✓
50mm or 63mm outlet connection (depending on pump type)*	✓	✓	✓	✓	✓
110mm services duct	✓	✓	✓	✓	✓
Integrated lifting eyes for ease of handling and installation	✓	✓	✓	✓	✓
Double sealed 600x600mm galvanised steel manhole cover, c/w locking screws	✓	✓	✓	✓	✓
Brass gate valve and PVC Union connection for ease of servicing	✓	✓	✓	✓	✓
Stainless steel pump lifting chain(s)	✓	✓	✓	✓	✓
Pump options available for water, effluent and sewage	✓	✓	✓	✓	✓
Non-return valve on all pumps	✓	✓	✓	✓	✓
Single and twin pump configurations		✓	✓	✓	✓
Control panel and float switches (twin pump configurations)		✓	✓	✓	✓
High-level alarm (twin pump configurations)		✓	✓	✓	✓
Guide rails (grinder pumps)		✓	✓	✓	✓

Please Note: All tank capacities are brimful. All information contained herein is understood to be correct at time of publication. Harlequin reserve the right to amend product specification without notice.